## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

## **LISTING OF CLAIMS:**

Claims 1-4 (canceled).

5. (currently amended): The A sealing bearing apparatus as set forth in claim 1, comprising:

an inner race dividable in an axial direction;

an outer race dividable in the axial direction;

tapered rollers in four rows rotatably disposed between the inner race and the outer race;

<u>and</u>

a sealing device for sealing a space between the inner race and the outer race;

the sealing device having an inner race member attached to the inner race and a sealing body attached to the inner race member,

wherein, when the inner race rotates at low speed, the sealing body serves as a contacting seal, and

when the inner race rotates at high speed, the sealing body serves as a non-contacting seal or reduces a contacting pressure due to deformation thereof by a centrifugal force,

wherein the sealing device further includes:

the outer race member; and

## PRELIMINARY AMENDMENT

1.53(b) Divisional of Appln. No.: 09/680,687

the inner race member encircled by the outer race member, and the outer race member is defined with a circumferential groove in a bearing outside edge thereof.

Claims 6-11 (canceled).

12. (currently amended): The A sealing bearing apparatus as set forth in claim 7, comprising:

an inner race;

an outer race;

a sealing device for sealing a space between the inner race and the outer race; and device including:

an outer race member;

an inner race member encircled by the outer race and attached to the inner race; and
a sealing member furnished between the inner member and the outer member, the sealing
member having:

a sealing body attached to the inner race member; and

a sealing face part disposed on the outer race member,

wherein, when the inner race member is rotated at a predetermined speed or lower, the sealing body contacts the sealing face part, and

when the inner race member is rotated at a speed more than a predetermined speed, the sealing body reduces the contacting pressure to the sealing face part, or separates from the sealing face part such as to form a non-contacting seal in conjunction with the sealing face part,

wherein the outer race member is defined with a circumferential groove in a bearing outside edge thereof.

Claim 13 (canceled).

14. (currently amended): The A sealing bearing apparatus as set forth in claim 7 comprising:

an inner race;

an outer race;

rolling elements rotatably disposed between the inner race and the outer race; and a sealing device for sealing a space between the inner race and the outer race, the sealing device including:

an outer race member;

an inner race member encircled by the outer race and attached to the inner race; and a sealing member furnished between the inner member and the outer member, the sealing member having:

a sealing body attached to the inner race member; and a sealing face part disposed on the outer race member,

wherein, when the inner race member is rotated at a predetermined speed or lower, the sealing body contacts the sealing face part, and

when the inner race member is rotated at a speed more than a predetermined speed, the sealing body reduces the contacting pressure to the sealing face part, or separates from the sealing face part such as to form a non-contacting seal in conjunction with the sealing face part,

wherein the sealing body is positioned at a side of an interior space of the bearing with respect to the sealing face part.

Claims 15-17 (canceled).